



NOTE:
 JAMB COLUMNS AND HEADER BEAM MUST BE ON THE SAME PLANE. HYDRAULIC POWER UNIT CAN BE MOUNTED AS DESIRED WITH ADVANCE NOTICE.

- PARTS:**
- (1) HYDRAULIC POWER UNIT EQUIPPED WITH A CHECK VALVE, RESERVOIR FILTER, AND A MINIMUM OUTPUT OF 1,000 PSI.
 - (2) DOUBLE ACTING REBUILDABLE HYDRAULIC CYLINDERS WITH A MINIMUM RATING OF 3,000 PSI.
 - (4) BRAIDED FLEXIBLE HYDRAULIC LINES WITH A MINIMUM RATING OF 3,000 PSI.
 - (1) FLOW CONTROL VALVE WITH A MINIMUM RATING OF 3,000 PSI.
 - (2) 50 / 50 MECHANICAL FLOW DIVIDERS FOR OPENING AND CLOSING WITH A MINIMUM RATING OF 3,000 PSI.
 - (1) IN-LINE RETURN LINE FILTER WITH A REPLACEABLE ELEMENT RATED AT A MINIMUM OF 1,000 PSI.
 - (3) 1" Ø CRS FLOOR PINS W/ 3" LG. SLEEVES (INCREASED AS NEEDED)
 - (5) THREE BARREL HINGES (INCREASED IN ACCORDANCE WITH DOOR DIMENSIONS)
 - XX FEET EPDM 10" BOTTOM WEATHER SEAL
 - XX FEET EPDM 12" TOP WEATHER SEAL

ELEVATION FROM INSIDE LOOKING OUT

ELECTRICAL:
 2HP TO 5HP ELECTRIC MOTOR ELECTRIC PER JOB SPECIFICATIONS.
 #HM-1414NPHL6 12 X 12 X 6 ELECTRICAL ENCLOSURE W/ MANUAL OPEN, & MANUAL CLOSE BUTTONS. LOAD HOLDING WHEN NOT IN OPERATION.

PAINT:
 GRAY OXIDE PRIMER

STEEL:
 TOP BEAM: 4 X 2 X 3/4"
 INTERMEDIATE HORIZONTALS: 4 X 2 X 11GA.
 VERTICAL STILES: 4 X 2 X 3/4"
 INTERIOR VERTICALS: 4 X 2 X 11GA.
 BOTTOM EXTERIOR TRUSSES: 4 X 2 X 11GA.
 BOTTOM BEAM: 4 X 4 X 3/4"
 ALL OTHERS: 4 X 2 X 11GA.

EST. WEIGHT:	WIND LOAD:	APPROVED:	DATE:	WELL BILT INDUSTRIES
ACTUAL WEIGHT:	ELECTRIC:	REVISED:	DATE:	TEL: 352-528-5566 FAX: 352-528-5614
		DRAWN:	DATE:	CUSTOMER:
		S. WILLIAMS	02-04-08	HYDRA-EZE TYPICALS
				PROJECT:
				NOT FOR CONSTRUCTION